

HITRE SPOJKE 7.2



TEHNIČNI PODATKI

VELIKOST	DN 7,2
PRETOK	2000 NI/min
MATERIAL	Medenina nikljana, CW614N/CW617N
DELOVNI TLAK	0 - 12 bar
TEMPERATURN OBMČJE	-20 / +70°C
MEDIJ	Komprimiran zrak (drugi mediji na vprašanje)

VTIČNICE ZUNANJI NAVOJ



HSF 7,2-014Z
HSF 7,2-038Z
HSF 7,2-012Z

VTIČNICE NOTRANJI NAVOJ



HSF 7,2-014N
HSF 7,2-038N
HSF 7,2-012N

VTIČNICE S SMREKICO



HSF 7,2-6N
HSF 7,2-7N
HSF 7,2-8N
HSF 7,2-9N
HSF 7,2-10N
HSF 7,2-12N
HSF 7,2-13N

VTIČNICE S PRIKLJUČKOM IN VZMETJO



HSF 7,2-6/4V
HSF 7,2-8/5V
HSF 7,2-8/6V
HSF 7,2-10/6,5V
HSF 7,2-10/8V
HSF 7,2-12/8V
HSF 7,2-12/10V

VTIČI Z ZUNANJIM NAVOJEM



HSM7,2-014Z
HSM7,2-038Z
HSM7,2-012Z

VTIČI Z NOTRANJIM NAVOJEM



HSM7,2-014N
HSM7,2-038N
HSM7,2-012N

VTIČI S SMREKICO



HSM7,2-6N
HSM7,2-7N
HSM7,2-8N
HSM7,2-9N
HSM7,2-10N
HSM7,2-12N
HSM7,2-13N

VTIČI S PRIKLJUČKOM IN VZMETJO



HSM7,2-6/4V
HSM7,2-8/5V
HSM7,2-8/6V
HSM7,2-10/6,5V
HSM7,2-10/8V
HSM7,2-12/8V
HSM7,2-12/10V

KODA ZA NAROČILO

